



Configuración del modelo

HGP	1A	2	R	N	S
1	2	3	4	5	6

1 HGP

HIFROSH Gear Pump

2	Montaje	SAE AA
3	Desplazamiento	1,2,3,4,5,6,8
4	Rotación	(R) derecha/(L) izquierda
5	Puertos	(N) npt omit/(G) bsp
6	Flecha	(S) recta 12.7 mm omit

Modelo	Desplazamiento cm ³ /rev	Galonaje @1800 rpm	A	B	Velocidad Max/Min	Presión Cont/Max (bar)	C Inlet	D Outlet
HGP-1A-1R	1.0	0.5	69.5	33.5	1000/4500	210/250	3/8" npt	3/8" npt
HGP-1A-2R	2.1	1.0	72	34.8	600/4500	210/250	3/8" npt	3/8" npt
HGP-1A-3R	3.0	1.4	77.5	37.5	600/4500	210/250	3/8" npt	3/8" npt
HGP-1A-4R	4.2	2.0	79.5	38.5	600/4500	210/250	3/8" npt	3/8" npt
HGP-1A-5R	5	2.4	83.5	40.5	600/3200	210/250	3/8" npt	3/8" npt
HGP-1A-6R	6.2	2.9	87.5	42.5	600/3200	210/250	3/8" npt	3/8" npt
HGP-1A-8R	7.8	3.7	93.5	45.5	600/3200	170/210	3/8" npt	3/8" npt