



| Type | Displacement c.c. | Pressure Mpa | | Speed | | | L (mm) | Inlet (mm) |
|------------------------|----------------------|--------------|------|-------|------|------|--------|------------|
| | | Rated | Peak | Rated | Max. | Min. | | |
| VNK-1-0.8-02-B-38-OR-A | 0.8 | 25 | 29 | 2000 | 3500 | 600 | 32 | G3/8 |
| VNK-1-1.1-02-B-38-OR-A | 1.1 | 25 | 29 | 2000 | 3500 | 600 | 33 | |
| VNK-1-1.3-02-B-38-OR-A | 1.3 | 25 | 29 | 2000 | 3500 | 600 | 33.5 | |
| VNK-1-1.6-02-B-38-OR-A | 1.6 | 25 | 29 | 2000 | 3500 | 600 | 34 | |
| VNK-1-1.8-02-B-38-OR-A | 1.8 | 25 | 29 | 2000 | 3500 | 600 | 34.5 | |
| VNK-1-2.1-02-B-38-OR-A | 2.1 | 25 | 29 | 2000 | 3500 | 600 | 35 | |
| VNK-1-2.7-02-B-38-OR-A | 2.7 | 25 | 29 | 2000 | 3500 | 600 | 36 | |
| VNK-1-3.2-02-B-38-OR-A | 3.2 | 25 | 29 | 2000 | 3500 | 600 | 37 | |
| VNK-1-3.7-02-B-38-OR-A | 3.7 | 25 | 29 | 2000 | 3500 | 600 | 38 | |
| VNK-1-4.2-02-B-38-OR-A | 4.2 | 25 | 29 | 2000 | 3500 | 600 | 39 | |
| VNK-1-4.8-02-B-38-OR-A | 4.8 | 23 | 27 | 2000 | 3500 | 600 | 40 | |
| VNK-1-5.8-02-B-38-OR-A | 5.8 | 23 | 27 | 2000 | 3500 | 600 | 42 | |
| VNK-1-8.0-02-B-38-OR-A | 8 | 18 | 23 | 2000 | 3500 | 600 | 46 | |
| VNK-1-9.2-02-B-38-OR-A | 9,2 | 15 | 19 | 2000 | 3500 | 600 | 48 | |

Rotation: A Left C Right

Dimensions:

